



Canfornav Inc.

A member of the Canadian Forest Navigation Group

M/V Pochard - Dimensions & Particulars

Built 2003, Shanghai Shipyard, China

Call Sign: V2BY3

Type: SDSTBC - Lakes fitted

Class: Germanischer Lloyd 100 A5 E1

IMO #: 9262534



Main Dimensions

DWT:	37,020MT
GT:	22,655MT
NT:	12,073MT
LOA:	199.99M
Beam:	23.7M
DM:	15.3M
Draft (SSW):	11.27M
Airdraft:	34.54M (Without holds flooded but fully ballasted)

Hold Capacities (Grain / Bale) M3

Hold 1:	5,176.4	5,124.6
Hold 2:	8,290.8	8,207.9
Hold 3:	8,139.2	8,057.8
Hold 4:	8,025.9	7,945.6
Hold 5:	8,025.9	7,945.6
Hold 6:	5,120.5	5,069.3
Total:	42,778.7	42,350.8

Hold Dimensions

Hold 1:	19.20M x 21.4M
Hold 2:	27.20M x 21.40M
Hold 3:	27.20M x 21.40M
Hold 4:	27.20M x 21.40M
Hold 5:	27.20M x 21.40M
Hold 6:	19.20M x 21.40M

Hatch Dimensions

Hatch 1:	12.0M x 15.6M
Hatch 2:	19.2M x 17.6M
Hatch 3:	19.2M x 17.6M
Hatch 4:	19.2M x 17.6M
Hatch 5:	19.2M x 17.6M
Hatch 6:	12.8M x 17.6M
Type:	MacGregor high stowing & folding, operated by external hydraulic cylinders.

Machinery & Consumption

Engine:	STX Man B&W 6S46MC-C 7,200KW / 9,655BHP @ 118.2RPM
Speed:	ABT 13.5KT
Consumption:	ABT 34.5MT IFO 380 CST at sea / ABT 2MT idle / 4.5MT working in port.
Bowthruster:	900KW / 1,224BHP
Gear:	4 x 40MT

All details are given in good faith, but without guarantee.