



**Canfornav Inc.**

**A member of the Canadian Forest Navigation Group**



### M/V Tufty - Dimensions & Particulars

Built 2009, Shanhaiguan Shipyard, China

Call Sign: 5BMK2

Type: SDSTBC - Lakes fitted

Class: Germanischer Lloyd 100 A5 E1

IMO #: 9393163

#### Main Dimensions

DWT:	30,803MT
GT:	19,814MT
NT:	10,208MT
LOA:	185M
Beam:	23.7M
DM:	14.6M
Draft (SSW):	10.416M
Airdraft:	37.8M (Without holds flooded but fully ballasted)

#### Hold Capacities (Grain / Bale) M3

Hold 1:	4,662.8	4,522.9
Hold 2:	7,675.2	7,445.0
Hold 3:	7,400.4	7,178.4
Hold 4:	6,241.6	6,054.4
Hold 5:	7,397.2	7,175.3
Hold 6:	5,257.7	5,100.0
Total:	38,634.9	37,476.0

#### Hold Dimensions

Hold 1:	19.00M x 14.20M
Hold 2:	23.70M x 20.00M
Hold 3:	21.40M x 20.00M
Hold 4:	22.90M x 20.00M
Hold 5:	21.40M x 20.00M
Hold 6:	20.00M x 20.00M

#### Hatch Dimensions

Hatch 1:	10.4M x 13.2M
Hatch 2:	19.2M x 17.4M
Hatch 3:	19.2M x 17.4M
Hatch 4:	16.0M x 17.4M
Hatch 5:	19.2M x 17.4M
Hatch 6:	13.6M x 17.4M
Type:	MacGregor high stowing & folding, operated by external hydraulic cylinders.

#### Machinery & Consumption

Engine:	STX Man B&W 6S46MC-C 7,200KW / 9,655BHP @ 118.2RPM
Speed:	ABT 13.5KT
Consumption:	ABT 25.5MT IFO 380 CST at sea / ABT 2.5MT idle / 4MT working in port.
Bowthruster:	900KW / 1,224BHP
Gear:	3 x 30MT

All details are given in good faith, but without guarantee.